











RIG DATA SHEET

Dando 3000

DRILLING TYPES	Cable percussive drilling
SAMPLING & TESTING METHODS	SPT, U100, UT100
GEOLOGY/STRATA	Superficial deposits: Gravels, Sands, Silts, Clays (To prove) Bedrock geology: Mudstone, Sandstone, Siltstone, other rock
ADDITIONAL USES	Piston sampling Packer testing Falling head testing Gas & groundwater monitoring well installations





Dando 3000 continued



SAMPLING DIAMETER	150mm - 300mm
TRANSPORT LENGTH	8500mm
TRANSPORT HEIGHT	1860mm
TRANSPORT WIDTH	1860mm
WORKING LENGTH	4800mm
WORKING HEIGHT	6550mm
WORKING WIDTH	2100mm
SOUND LEVEL	Approx. 92 dB
CREW SIZE	2 man crew
VEHICLES	1 vehicle, 1 trailer
IDEAL WORKING AREA	4000mm x 12000mm

This data sheet is for general guidance only and should be used alongside advice provided by RGS.



Need more help?

GET IN TOUCH WITH US TODAY

TELEPHONE: 01484 **604354**

FAX: 0843 51 599 30

EMAIL: **enquiries**@rogersgeotech.co.uk











